



Reviewed: January 2015

FT Technologies Ltd
Church Lane
Teddington
Middlesex TW11 8PA
England

Environmental Safety Data Sheet for FT702LT and LTD Wind Sensors.

Description: The FT702LT and LTD are combined wind speed and direction sensors. The case is hard anodised 6026 T6 aluminium alloy surrounding a hydrophobic acoustic cavity and containing printed circuit boards, components and connectors together with associated wiring.

Tel +44 (0)20 8943 0801
Fax +44 (0)20 8943 3283
Email sales@fttech.co.uk
www.fttech.co.uk

RoHS-2 compliance

Max concentration 0.1% by weight.

Lead (Pb)	None used**
Mercury (Hg)	None used
Hexavalent Chrome	None used
Poly-Brominated Biphenyls	None used
Poly-Brominated Diphenyl Ethers	None used

Max concentration 0.01% by weight.

Cadmium (Cd)	None used
--------------	-----------

**It must be noted that the regulatory requirements of the China RoHS regulations, unlike the EU regulations, require testing to homogenous component level by a certified Chinese facility.

Most EU RoHS compliant SMT resistors contain in excess of 1000 ppm of lead by weight at the component level. The lead (Pb) is contained in the lead oxide of the primary glass layer of the resistor body and in the resistive layer. It is not technologically possible to produce SMT resistors without the use of lead in oxide form in various parts of the component

WEEE 2013 Compliance

FT Technologies are nominally exempt from this since our product is designed to generally form part of a larger installation e.g. a wind turbine. We do however transfer any residual obligation for safe disposal under this legislation to the purchaser of the sensor. This is because we have no knowledge of the end user or what environmental legislation may pertain at end of life.

We do however undertake to dispose of any sensors returned to us for this purpose under the UK rules currently prevailing and will certify to this effect.

REACH Compliance to Candidate List: 161

The sensors are defined as articles under this legislation. No Substances of Very High Concern (SVHC's) are used by FT and none have been notified to us by any of our suppliers.

General

No radioactive materials are used in this device.

No materials known to promote severe or chronic allergic reactions (i.e. beryllium, antimony, arsenic, bismuth, vanadium, asbestos, etc.) are used in the sensors construction.

Signed

P. Martin-Loat
Quality & Product Assurance Manager

Information content follows the Material Composition Declaration for Electronic Products IPC-1752A with Amendments 1 and 2 and the Japanese Green Procurement Survey Standardization Initiative.

